

Telehandler / Zoom Boom

Used Telehandler Texas - Telehandlers are commonly known by a variety of names such as Cherry pickers, telescopic handlers, boom lifts and teleporters. These machines are utilized in agriculture and many different industries. This machine functions similarly to a crane and a forklift with the ability to extend upward and forward. The operator can utilize a variety of attachments at the end of the articulating boom to complete different jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The pallet forks are the most popular telehandler attachment. They allow the operator to transport loads to and from locations that are considered unreachable with a regular forklift. These machines enable cargo pallets to be unloaded and loaded from a trailer and placed on rooftops, racking or other high and hard to access locations. Often, high rooftop locations would need a crane although, telehandlers can accomplish these tasks much more efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. Within agriculture, the bucket or bucket grab is among the most popular attachments. Transporting items from unreachable places that cannot use a backhoe loader or a wheeled loader is one of the main advantages of using a telehandler. Telehandlers can directly access trailer units with high sides, hoppers or applications that would typically need a conveyor or loading ramp. Relying on one piece of equipment to complete a variety of jobs saves time, money and storage. Telehandler machines can work in conjunction with a crane jib. Many attachments can be used such as power booms, grain and dirt buckets and rotators. The agricultural models can use three-point linkage and power take-off to make telehandlers multi-tasking. However, the main advantage of the telehandler is additionally its' largest limitation. The boom raises or extends with heavy loads, acting as a lever. Even with rear counterweights, this machine may become unstable from time to time; decreasing the lift capacity when the distance between the center of the load and the front of the wheels or the working radius increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. For instance, a telehandler with a five thousand pound capacity may be capable of safely lifting as little as four hundred pounds fully extended with a low boom angle with a retracted boom. The same piece of equipment with a five thousand pound lift capacity and retracted boom may be capable as supporting up to ten thousand pounds once the boom is raised to seventy degrees. These machines are equipped with a load chart to help outline which tasks are safely possible. These charts take the boom height, angle and weight into account. Updated telehandler models have computers and sensors. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. Front stabilizers that enhance the lifting capacity of the machine while stationary can make a huge difference. Another option is a stabilizing rotary joint between lower and upper frames, often referred to as a mobile crane that can additionally utilize a bucket. There are compact telehandler models that differ in boom design, size, reach and weight. If the machine weighs in at eleven thousand pounds or less, it can be part of the compact category. Compact models feature a two- stage boom design in comparison to the three or four boom design that is common with larger units. A low pivot boom ensures better operator visibility for transporting loads on compact units. Compact models are skinnier and have thinner dimensions. The compact units offer a reach capacity between thirteen to twenty feet and a lifting capacity ranging from five thousand to seven thousand pounds. There are many different applications this machine is suitable for working in. Telehandlers can function as a pick and place unit or a tool carrier. This machine is often used in locations that are cramped and tight. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. These units can be useful for accessing internal building locations. Compact telehandlers are commonly used in nurseries, landscaping, multi-story construction, building strip malls and garages, masonry, erecting steel and more. Telehandlers are employed by agri-business and farming applications to

complete many jobs. Telehandlers can be found with two and four-wheel drive and crab steering capabilities. The unit can travel over longer ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. The four-wheel drive models offer the ability to traverse more difficult terrain and provide a tighter turning radius. Crab steering is responsible for the increased maneuverability, allowing the front and rear wheels to shift forty-five degrees to the right or left. There are a variety of cab interior options available for compact telehandlers. There is a rollover protective cage to enhance safety on less expensive models. Newer units come with windshield wipers, a defroster, a heater and a totally enclosed cab. Operators enjoy spacious accommodation for ultimate comfort. Additional options including satellite radio, air conditioning, armrests, cup holders, suspension seats and tilt steering are available. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. The different attachments allow the machine to be capable of many options. All of these attachments enable the machine to conduct a variety of jobs. Compact machines conduct ground-engaging jobs. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. Light and heavy-duty buckets can be used to move items, augers can plant trees or drill holes, rotating and side-shifting fork carriages facilitate pick-and-place, truss booms are in place for extending reach, sweeping brooms and crane hooks are other popular attachments. Skid steer options are made for compact telehandler designs and ultimate versatility.